

task_ddjurcpk494go2q1_with_calculation

Student Group

First Name	Surname	Matrikel Nr.

Table of Contents

Exercise E5 Fields of an coax Cable (written test, approx. 12 % of a 120-minute written test, SS2024) 2

electric field, magnetic field, exam ee2 SS2024

Exercise E5 Fields of an coax Cable (written test, approx. 12 % of a 120-minute written test, SS2024)

2. On the graph of the magnitude of the electric field $E(r)$ with radial distance r of the coax cable (dia 4.0 mm) shows the cross-section (0.5 mm) of the inner conductor (0.6 mm) centered diagram. Use appropriate dimensions and label for the diagram.

Path

Inner conductor: $+3.3 \text{ mA}$, $+10 \text{ nC}$ (current into the plane of the diagram)

Outer conductor: -3.3 mA , 0 nC (current out of the plane of diagram)

- for $(0.1 \text{ mm} | 0)$: $E_{(r_i)} = 5.28 \dots \text{ V/m}$
- for $(0.55 \text{ mm} | 0)$: $E_{(r_o)} = 0.985 \dots \text{ V/m}$

The magnitude of the electric displacement field D can be calculated by: $\int D \cdot dA = Q_{enc}$.

In general, the E -field is proportional to $\frac{1}{r}$ for the situation between both conductors (here for simplicity without the round endings). Here, the position radius of the enclosing area is the surface of a cylindrical shape (here for simplicity without the round endings).

For the E -field as a function of the radius r of the enclosing area D is much simpler to calculate. This leads to: $D(r) = \frac{Q_{enc}}{A} = \frac{Q_{enc}}{\pi \cdot r^2}$.

This is proportional to the area within this radius. Therefore, the formula $H = \frac{I_{enc}}{2\pi \cdot r}$ gets $H(r) = \frac{I_{enc}}{2\pi \cdot r}$.

So, we get for D at $r = 0.1 \text{ mm}$ and $r = 0.55 \text{ mm}$. This leads to a formula proportional to r .

- For r within the outer conductor one also gets a linear proportionality with a different approach: $D(r) = \frac{Q_{enc}}{2\pi \cdot r} = \frac{10 \cdot 10^{-9} \text{ C}}{2\pi \cdot 0.1 \cdot 10^{-3} \text{ m} \cdot 0.5 \cdot 10^{-3} \text{ m}}$
- $D_{(r_o)} = \frac{Q}{2\pi \cdot r_o} = \frac{10 \cdot 10^{-9} \text{ C}}{2\pi \cdot 0.55 \cdot 10^{-3} \text{ m} \cdot 0.5 \cdot 10^{-3} \text{ m}}$

Hint: For the direction, one has to consider the sign of the enclosed charge. By this, we see that the D -field is positive. But here, again only the magnitude was questioned!

.. What is the magnitude of the magnetic field strength H at $(0.1 \text{ mm} | 0)$ and $(0.55 \text{ mm} | 0)$?

Path

The magnitude of the magnetic field strength H can be calculated by: $H = \frac{I}{2 \pi \cdot r}$

So, we get for H_{i} at $r_{\text{i}} = 0.1 \text{ mm}$, and H_{o} at $r_{\text{o}} = 0.55 \text{ mm}$:

$$\begin{aligned} H_{\text{i}} &= \frac{I}{2 \pi \cdot r_{\text{i}}} = \frac{+3.3 \text{ A}}{2 \pi \cdot 0.1 \cdot 10^{-3} \text{ m}} \\ H_{\text{o}} &= \frac{I}{2 \pi \cdot r_{\text{o}}} = \frac{+3.3 \text{ A}}{2 \pi \cdot 0.55 \cdot 10^{-3} \text{ m}} \end{aligned}$$

Hint: For the direction, one has to consider the right-hand rule. By this, we see that the H -field on the right side points downwards.

Therefore, the sign of the H -field is negative.

But here, only the magnitude was questioned!

From:

<https://mexle.te.hs-heilbronn.de/> - **MEXLE Wiki**

Permanent link:

https://mexle.te.hs-heilbronn.de/ee2/task_ddjurcpgk494go2q1_with_calculation

Last update: **2024/07/15 21:37**

