

# task\_ddjurcpk494go2q1\_with\_calculation

## Student Group

First Name	Surname	Matrikel Nr.

## Table of Contents

Exercise E1 Fields of an coax Cable (written test, approx. 12 % of a 120-minute written test, SS2024) ..... 2

electric field, magnetic field, exam ee2 SS2024

Exercise E1 Fields of an coax Cable (written test, approx. 12 % of a 120-minute written test, SS2024)

2. Plot the graph of the magnitude of the electric field  $E(r)$  with  $r$  in  $\text{mm}$ . The dia  $d_1 = 0.6 \text{ mm}$  shows the cross-section of the inner conductor with  $(0.6 \text{ mm} | 0)$  in center. The diagram also depicts dimensions and labels for the diagram that appears:

• Inner conductor:  $+3.3 \text{ mA}$ ,  $+10 \text{ nC}$  (current into the plane of the diagram)  
 • Outer conductor:  $-3.3 \text{ mA}$ ,  $0 \text{ nC}$  (current out of the plane of diagram)  
 • for  $(0.1 \text{ mm} | 0)$ :  $E_{\text{in}} = 3.28 \dots \text{ V/m}$   
 • for  $(0.55 \text{ mm} | 0)$ :  $E_{\text{out}} = 0.985 \dots \text{ V/m}$

The magnitude of the electric displacement field  $D$  can be calculated by:  $\int D \cdot dA = Q_{\text{enc}}$ .

In general, the  $E$ -field is proportional to  $\frac{1}{r}$  for the situation between both conductors (here for simplicity without the round endings). Here, the position radius of the enclosing area is the surface of a cylindrical shape (here for simplicity without the round endings). So, the  $E$ -field is proportional to the surface of the cylinder. This leads to:  $D(x) = \frac{Q_{\text{enc}}}{A} = \frac{Q_{\text{enc}}}{\pi \cdot r^2}$ . This is proportional to the area within this radius. Therefore, the formula  $H = \frac{D}{\epsilon_0}$  gets  $H(x) = \frac{Q_{\text{enc}}}{\epsilon_0 \cdot \pi \cdot r^2} \cdot x$ . So, we get for  $D$  at  $r = 0.1 \text{ mm}$  and  $D$  at  $r = 0.55 \text{ mm}$ . This leads to a formula proportional to  $x$ .

For  $x$  within the outer conductor one also gets a linear proportionality with a different approach:  $D(x) = \frac{Q_{\text{enc}}}{2 \cdot \pi \cdot r \cdot l} = \frac{10 \cdot 10^{-9} \text{ C}}{2 \cdot \pi \cdot 0.1 \cdot 10^{-3} \text{ m} \cdot 0.5 \cdot 10^{-3} \text{ m}}$   
 $D_{\text{out}} = \frac{Q}{2 \cdot \pi \cdot r \cdot l} = \frac{10 \cdot 10^{-9} \text{ C}}{2 \cdot \pi \cdot 0.55 \cdot 10^{-3} \text{ m} \cdot 0.5 \cdot 10^{-3} \text{ m}}$

Hint: For the direction, one has to consider the sign of the enclosed charge. By this, we see that the  $D$ -field is positive. But here, again only the magnitude was questioned!

.. What is the magnitude of the magnetic field strength  $H$  at  $(0.1 \text{ mm} | 0)$  and  $(0.55 \text{ mm} | 0)$ ?

The magnitude of the magnetic field strength  $H$  can be calculated by:  $H = \frac{I}{2 \pi \cdot r}$

So, we get for  $H_{\text{i}}$  at  $r_{\text{i}} = 0.1 \text{ mm}$ , and  $H_{\text{o}}$  at  $r_{\text{o}} = 0.55 \text{ mm}$ :

$$\begin{aligned} H_{\text{i}} &= \frac{I}{2 \pi \cdot r_{\text{i}}} = \frac{+3.3 \text{ A}}{2 \pi \cdot \{0.1 \cdot 10^{-3} \text{ m}\}} \\ H_{\text{o}} &= \frac{I}{2 \pi \cdot r_{\text{o}}} = \frac{+3.3 \text{ A}}{2 \pi \cdot \{0.55 \cdot 10^{-3} \text{ m}\}} \end{aligned}$$

Hint: For the direction, one has to consider the right-hand rule. By this, we see that the  $H$ -field on the right side points downwards.

Therefore, the sign of the  $H$ -field is negative.

But here, only the magnitude was questioned!

From:

<https://mexle.te.hs-heilbronn.de/> - MEXLE Wiki

Permanent link:

[https://mexle.te.hs-heilbronn.de/electrical\\_engineering\\_and\\_electronics/task\\_ddjurcpk494go2q1\\_with\\_calculation?rev=172107227](https://mexle.te.hs-heilbronn.de/electrical_engineering_and_electronics/task_ddjurcpk494go2q1_with_calculation?rev=172107227)

Last update: 2024/07/15 21:37

